

OEL-KLEEN ABSORBENTS OIL ONLY Bonded Roll

OIL - WHITE:

Property: Hydrophobic, absorbs hydrocarbon-based liquids (oil), water-repellent

Suitable for: Oils, gasoline, diesel, solvents, and petroleum

OEL-KLEEN Sorbents offers the right solution for everyday spills and major oil accidents that have a significant impact on people and the environment.

OEL-KLEEN Sorbents provide lasting protection, for example around or under machines and aggregates, and keep the workplace clean and safe.

- Optimal suction power for oils and hydrocarbonskostensparend
- Safe and non-slip
- absorbs oil, not water
- Absorbs mineral oil, hydrocarbons, and other oil-based liquids without absorbing a drop of water!
- No liquid remains, even when the mat is completely saturated..

Qualities / Type

The higher the durability, the stronger and longer the product can be used and remain in service. Depending on the application, you should therefore consider whether you need extremely high durability or whether normal quality is sufficient for your purposes.

Our nonwovens are available in various qualities:

Bonded: Single-layer structure with high absorbency, additionally bonded by weld spots)

For most everyday applications in the workplace. Highly absorbent binding fleece without additional reinforcement on the top or bottom. Suitable for economical use in cleaning up small spills or for everyday use in cleaning, maintenance, and repair work..

The information is based on our current knowledge and experience.

The technical data sheet describes products in terms of their chemical composition.

The information does not constitute a guarantee of properties. Revised on: February 9, 2026

Item No.	Form	Article Description	Perforation		quality	textile starch	Weight/ Packaging unit	dimension	VPE	packaging	Absorption max (l/pack)
			along	quer		g/m ²					

OIL ONLY BONDED Rolle

1021123	Rolle		1	every 40 cm	bonded	320	10,24	0,80 x 40 m	1	PE-foil	159
1021146	Rolle		1	every 50 cm	bonded	280	11,20	1,0 x 44 m	1	PE-foil	174
1021147	Rolle		1	every 50 cm	bonded	280	5,6	0,5 x 44 m	1	PE-foil	87
1021148	Rolle		1	every 50 cm	bonded	280	4,48	0,4 x 44 m	1	PE-foil	69



The information is based on our current knowledge and experience.

The technical data sheet describes products in terms of their chemical composition.

The information does not constitute a guarantee of properties. Revised on: February 9, 2026