

# OEL-KLEEN ABSORBENTS

## Universal Bonded Rolle

### UNIVERSAL - GREY:

property: Hydrophilic, absorbs almost all liquids

Suitable for: Oils, coolants, lubricants, antifreeze, oil-water emulsions, and other aqueous liquids, as well as non-aggressive acids and alkalis

OEL-KLEEN Sorbents provide lasting protection, for example around or under machines and aggregates, and keep the workplace clean and safe..

- For absorbing all industrial liquids
- High absorption capacity - lower binder requirement
- Lightweight - makes transport easier and reduces waste
- Clean—no dirt, no dust, no sweeping
- Environmentally friendly - residue-free combustion
- Can be used preventively – prevents the spread of pollutants
- Economical—reduced labor and low disposal costs.

### Examples of use:

- Absorption of all industrial liquids
- Ideal for leaks and maintenance work
- Can be used preventively
- Increased cleanliness and safety in the workplace
- Absorption on machine parts that are difficult to access.

### Suitable for:

- in automotive repair shops
- in industrial plants on machines that are difficult to access.

The information is based on our current knowledge and experience.

The technical data sheet describes products in terms of their chemical composition.

The information does not constitute a guarantee of properties.

Revised on: 10.02.2026

### Qualities / Type

The higher the durability, the stronger and longer the product can be used and remain in service. Depending on the application, you should therefore consider whether you need extremely high durability or whether normal quality is sufficient for your purposes..

Our nonwovens are available in various qualities:

**Bonded:** Single-layer structure with high absorbency, additionally connected by weld spots (bonded)

For better fixation of the polypropylene layers

Highly absorbent binding fleece without additional reinforcement on the top or bottom. They are suitable for economical use in the removal of minor leaks or for daily use in cleaning, maintenance, and repair work.

| Item No.                      | Form  | Article description | Perforation |             | Qualität | Textilstärke     |               | Abmessung   | VPE | Verpackung | Absorption max (l/pack) |
|-------------------------------|-------|---------------------|-------------|-------------|----------|------------------|---------------|-------------|-----|------------|-------------------------|
|                               |       |                     | along       | crosswise   |          | g/m <sup>2</sup> | Gewicht / VPE |             |     |            |                         |
| <b>UNIVERSAL BONDED Rolle</b> |       |                     |             |             |          |                  |               |             |     |            |                         |
| 1021187                       | Rolle | -                   | without     | every 40 cm | bonded   | 280              | 9,4           | 0,38 x 44 m | 2   | PE-foil    | 32                      |



The information is based on our current knowledge and experience.

The technical data sheet describes products in terms of their chemical composition.

The information does not constitute a guarantee of properties.

Revised on: 10.02.2026