

OEL-KLEEN Universal absorber fine

Oil binding agent based on calcium silicate hydrate

Classification criterion for oil binding agent type III R

Oil and chemical binders for storing oils and other leaked fluids.
Suitable for traffic areas (oil Binder type III R).

For the cleaning and protection of industrial floors.

Suitable for hazardous oil traces on driving and runways from spreading, not water resistant and not floatable.

OIL KLEEN universal Binder fine create safe working conditions, is non-skid, non-toxic, non-flammable and leaves no residue.

Universal Binder fine for the sorption of organic and inorganic compounds, as

- Oils, oils, greases, and lubricants
- Lye
- Paints, lacquers
- Solvents, hydrocarbons

Avoid contact with strong acids and oxidizing agents.

- Binders for alkaline, alkaline substances (Leach)
- Binders for flammable and combustible fluids
- Oil Binder type III R
- Binders for aqueous and polar fluids

The product is chemically inactive compared to many other liquids.

Not to apply at: oxidative substances and hydrofluoric acid

Oil Binder requirements:

1 L absorbs 0,39 L Oil

1 KG absorbs 0,86 L Oil

1 KG absorbs 0,71 KG Oil



Item No	Content	Absorption per bag	Bulk density	Grain size	Pallet
1000007	40 L	15,6 L	454 g/l	0,125 – 1 mm	36 PE-bags